

HD Fire Exit Steel Door

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

HD Fire Exit Steel Door



Product Range

HD Fire Exit Steel Door

What Is It Made From

The HD Fire Exit Steel Door is 1.2mm Corrosion resistant Zintec/Aluzinc as standard. Infill of self supporting resin-impregnated honeycomb core as standard, with the option of mineral wool or Solid Timber

Typical Uses

Fire Exit Door

Security Level

Medium / High

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

HD Fire Exit Steel Door



Product Overview

Description

HD Fire exit Steel Door

Common Use

A Fire exit door to be used by the general public and provides safe and effective escape through the doorway with minimal effort and with out prior knowledge of operation.

Dimensions

Single openings from 690mm to 1390mm
Double openings from 1290mm to 2600mm
All at heights up to 2900mm

Finish

The HD Fire exit steel door Pre primed light grey BS10A05 as standard, Powder coat from standard range available also Woodgrain PVC Laminate, Stainless steel available

Specification of Build

Steel Door Leaf thickness of 48mm.

Door Infill of self supporting resin-impregnated honeycomb core as standard, with the option of mineral wool or Solid Timber

Door Frame folded from 1.6mm Zintec/aluzinc

Screw and tab construction with 4 no adjustable fixing feet per jamb, variable subframe supplied as standard to accommodate site tolerance of -0+30mm.
The frame is fitted with 4no dog bolts hinge as standard.

Threshold – As standard 15mm rebated threshold, optional 5mm driveable (DDA Compliant) 12.5mm 564a Aluminium (DDA Compliant)

Operation

Manual

Panic Hardware

Rim Panic Latch – Surface Mounted, single point rim panic latch

Mortice Panic Night Latch – a mortice night latch operated by an internal cross bar, providing medium security.

Can be fitted with external cylinder for external access

Two Point Panic Bolt – Surface mounted, two point bolting panic with full internal crossbar

Double Escape Door- The combination of the panic latch on the active leaf and a bolt on the inactive one allows independent escape.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
