

HD Louvred Steel Door

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

HD Louvred Steel Door



Product Range

HD Louvred Steel Door

What Is It Made From

HD Louvred Steel Door is 1.2mm Corrosion resistant Zintec/Aluzinc as standard

Typical Uses

Air venting Security Steel Door

Security Level

High

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

HD Louvred Steel Door



Product Overview

Description

HD Louvred Steel Door

Common Use

Commercial / Industrial

Dimensions

Single openings from 690mm to 1390mm
Double openings from 1290mm to 2600mm
All at heights up to 2900mm

Finish

HD Louvred Steel Door is Pre primed light grey BS10A05 as standard, Powder coat from standard range available.

Specification of Build

Steel Door Leaf thickness of 48mm.

Steel Door Blades made from 1.2mm Corrosion resistant Zintec/Aluzinc as standard. Door blades set at 45o and mounted at 50mm deep angle frame, which is mounted on a box section sub-frame.

Steel Door Frame folded from 1.6mm Zintec/aluzinc

Screw and tab construction with 4 no adjustable fixing feet per jamb, variable subframe supplied as standard to accommodate site tolerance of -0+30mm.

The frame is fitted with 3no class 13 stainless steel hinge with 2no security dog bolts.

Threshold – As standard 15mm rebated threshold, optional 5mm driveable (DDA Compliant) 12.5mm 564A Aluminium (DDA compliant)

Operation

Manual

Security

Single – Modular Mortice Lock

Double – with an addition of a flush bolt to inactive leaf

Optional Extras

Side and over panels for connecting windows available

A galvanised bird and vermin mesh can be supplied

Panic bolts / Latch

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
