

# Seceuro Range CD38 Built On

Technical Specifications



[www.hag.co.uk](http://www.hag.co.uk)  
Advice Line 0800 072 3444

# Seceuro Range CD38 Built On



## What is it made from

The Seceuro range offers an all Aluminium Construction

## Typical Uses or Specific Use

Typical uses are from serving areas, Cabinets, Office windows and Domestic Properties.

## Security Level

Medium to Low Security

## Benefit of product range

The Seceuro Range provides a high level of aesthetics Can be installed where headroom is restricted

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---

# Seceuro Range CD38 Built On



## Product Overview

### Description

Seceuro CD 38 Built On, CD38 is a double skin extruded aluminium non-vented slat.

### Variations

Perforated, punched, glazed (Up To 3000mm wide) & Insurance approved options available.

### Common use

Domestic / Commercial Windows, Doors, Surverys & Cabinets.

### Maximum Width

4000mm

### Dimensions

Nominally 38mm high x 9mm thick.

### Weight

8kg per square metre.

### Finish

White, brown or cream. Bottom slat - white, dark brown alternative standard RAL or BS colours at extra cost.



## Shutter Box Specification

### Construction

Roll formed aluminium in two sections; top and bottom boxes. Bottom box removable for installation and maintenance and Chamfered at 45°. The shutter box is assembled on die cast aluminium endplates.

### Box sizes

Clear opening height (to underside of box):

1535mm, box size 165mm

1820mm, box size 180mm

2595mm, box size 205mm

### Finish

White, dark brown. The CD38 Box can be powder coated to alternative standard RAL or BS colours at extra cost.

## Guide Rail Specification

### Construction

Ref - H30 Extruded aluminium with an integral box section for reinforcement and to facilitate fixing. High density 6mm pile brush seals for quiet and smooth operation. 60mm wide x 24mm deep

### Finish

White, dark brown Standard RAL or BS colours at extra cost.

### Security Features

Standard shutters lock automatically at the top when fully lowered. The bottom section of the shutter box is riveted after installation. The fixing screw heads are rendered unusable and are concealed behind cover caps. Optional 30 x 20 angle can be fixed on to the cill.

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---

# Seceuro Range CD38 Built On



## Operational Specification

### Swivel Belt Winder

- for shutters up to 15kg

The swivel winder coils the belt when it is pulled to open the shutter. The belt is 14mm wide and grey in colour. External shutters are supplied with a guide tube to protect the belt through the building wall.

### Geared Belt Winder

For shutters between 15kg and 25kg

1:3 ratio with removable handle for belt operated shutters.

### Rod Crank Operation

For shutters up to 25kg

Incorporates a geared rod crank handle 1500mm long which hangs vertically and secures into a clip when not in use. The gear is installed in the box, the gear ratio varies with shutter weight

### Spring Loaded

A counter balanced spring ensures controlled raising and Lowering with a key lock in-built at the bottom of the shutter for Security

### Single Phase Electric

Provision of a 13 amp fused spur is required for installation.

A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating.

Draw 240 volts and 0.5 - 2.5 amps dependant upon the shutter size

### Control

Standard security keyswitch or rocker switch.

Other controls are available on request.

### Override

A counter balanced spring ensures controlled raising and Lowering with a key lock in-built at the bottom of the shutter for Security

---

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

---

Visit our website for more information on HAG Roller Shutters [www.hag.co.uk/roller-shutters.html](http://www.hag.co.uk/roller-shutters.html)

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---