

Seceuro Range CD77 Built On

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Seceuro Range CD77 Built On



What is it made from

The Seceuro range offers an all Aluminium Construction

Typical Uses or Specific Use

Typical uses are from serving areas, Cabinets, Office windows and Domestic Properties.

Security Level

Medium to Low Security

Benefit of product range

The Seceuro Range provides a high level of aesthetics Can be installed where headroom is restricted

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Seceuro Range CD77 Built On



Product Overview

Description

Seceuro CD77 Built On, CD77 is a double skin foam filled aluminium non-vented slat. The CD77 slat can be mixed with the CD78 vision panel slat that has apertures of 80mm x 35mm with a polycarbonate insert to offer a partial vision section to the shutter.

Common use

Domestic window shutters/garage doors, medium security commercial and office applications.

Maximum Width

5400mm

Dimensions

Nominally 77mm high x 19mm thick..

Weight

5kg per square metre.

Finish

White, brown or light beige.

Bottom slat - white, dark brown. Other colours available on request.



Shutter Box Specification

Construction

Roll formed aluminium in two sections; top and bottom boxes. Bottom box removable for installation and maintenance and Chamfered at 45°. The shutter box is assembled on die cast aluminium endplates.

Box sizes

Clear opening height (to underside of box):

1550mm, box size 250mm

2600mm, box size 300mm

Finish

White, dark brown, Standard RAL or BS colours at extra cost.

Guide Rail Specification

Construction

90mm wide x 34mm With High density 4mm pile brush seals for quiet and smooth operation

Finish

White, dark brown, Standard RAL or BS colours at extra cost.

Acoustics

(Insulation 2.8 watts per m² Kelvin w/m²k)

Decibel reduction at 500HZ = 18

Decibel reduction at 1000MHZ = 2

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Seceuro Range CD77 Built On



Operational Specification

Spring Loaded

A counter balanced spring ensures controlled raising and Lowering with a key lock in-built at the bottom of the shutter for Security.

Single Phase Electric

Provision of a 13 amp fused spur is required for installation.

A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating.

Draw 240 volts and 0.5 - 2.5 amps dependant upon the shutter size

Control

Standard security keyswitch or rocker switch. Other controls are available on request.

Override

A Manual override should be priced and ordered separately for Shutters which are to be installed on exit doorways to permit Operation in the event of a power failure. This is usually only Operable from only one side.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

Visit our website for more information on HAG Roller Shutters www.hag.co.uk/roller-shutters.html

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
