

# Seceuro Range CD900 Built On

Technical Specifications



[www.hag.co.uk](http://www.hag.co.uk)  
Advice Line 0800 072 3444

# Seceuro Range CD900 Built On



## What is it made from

The Seceuro range offers an all Aluminium Construction

## Typical Uses or Specific Use

Typical uses are from serving areas, Cabinets, Office windows and Domestic Properties.

## Security Level

Medium to Low Security

## Benefit of product range

The Seceuro Range provides a high level of aesthetics Can be installed where headroom is restricted

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

# Seceuro Range CD900 Built On



## Product Overview

### Description

Seceuro CD900 Built On, CD900 is an open grille constructed of extruded aluminium bars and links.

### Common use

Internal shopfronts, kiosks, bars and serveries Where vision is required

### Maximum Width

5000mm

### Dimensions

150mm x 70mm Apertures.

### Weight

150mm x 70mm spacing 7kg per square metre

75mm x 70mm spacing 8kg per square metre

75 x 70mm spacing 8kg per square metre

### Finish

Satin silver anodised as standard.

Powder coated to standard RAL or BS colours at an extra cost

Regular or brick bond pattern. Solid slats can be included at extra cost for visual effect or extra strength.

Certain logos and designs can be incorporated in the construction of the grille



## Shutter Box Specification

### Construction

Roll formed aluminium in two sections; top and bottom boxes.

Bottom box removable for installation and maintenance and Chamfered at 45°.

The shutter box is assembled on die cast aluminium endplates.

### Box sizes

Clear opening height (to underside of box):

1400mm, box size 205mm

2550mm, box size 250mm

3700mm, box size 300mm

### Finish

White, dark brown, Alternative standard RAL or BS colours at an extra cost.

## Guide Rail Specification

### Construction

60mm x 29mm x 3mm - 90mm x 34mm x 3mm dependant on width and height.

Both with high density 4mm - 7mm pile brush seals.

### Finish

White, dark brown, Alternative standard RAL or BS colours at an extra cost.

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

# Seceuro Range CD900 Built On



## Operational Specification

### Spring Loaded

A counter balanced spring ensures controlled raising and Lowering with a key lock in-built at the bottom of the shutter for Security.

### Single Phase Electric

Provision of a 13 amp fused spur is required for installation.

A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating.

Draw 240 volts and 0.5 - 2.5 amps dependant upon the shutter size

### Control

Standard security keyswitch or rocker switch. Other controls are available on request.

### Override

A Manual override should be priced and ordered separately for Shutters which are to be installed on exit doorways to permit Operation in the event of a power failure. This is usually only Operable from only one side.

---

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

---

Visit our website for more information on HAG Roller Shutters [www.hag.co.uk/roller-shutters.html](http://www.hag.co.uk/roller-shutters.html)

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---