

Seceuroguard Range 1001

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Seceuroguard Range 1001



What is it made from

The Seceuroguard range offers an all steel Construction

Typical Uses or Specific Use

Typical uses range from home and office windows to commercial shopfronts

Security Level

Medium to Low Security

Benefit of product range

This range benefits from Ease of Operation, low maintenance and fully retractable allowing excellent through vision when locked.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Seceuroguard Range 1001



Product Overview

Description

The Seceuroguard range offers an all steel Construction. This range benefits from Ease of Operation, low maintenance and fully retractable allowing excellent through vision when locked.

Common use

Where insurers have specified LPCB level 1 protection

Weight

19kg per metre Square

Dimensions

15mm x 14mm x 1.2mm cold rolled steel sections

Finish

Standard RAL Stock Colours available

Top Track

45mm x 40mm Steel Top Track (Additional 45mm x 20mm box section required if face fixed)

Stacking Size

Approximately 15% of overall width (View standard drawing for specific dimensions)

Locking

4 Point locking system with shielding

Operation

Manual operatio

Available Option

Standard "X" Lattice

"S" Lattice

Folding Bottom Track

Hinge aside stacking option

Note

The validity of the LPCB certification is dependent upon each security gate being installed in accordance with the requirements of LPS1175

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
