



Reveal fixed

Face fixed

- Product:** C2 Armourguard
- Operation:** Single phase tube motor with override
- Operator:** security keyswitch
- Power requirements:** 13amp fused spur within 1 metre of opening
- Fixing:** Reveal fixed or Face fixed
- Finish:** Plasticol coated steel

- Head plate sizes:**
 Overall height: Upto 2000mm Head plate = 254mm
 Overall height: Upto 3000mm Head plate = 305mm
 Overall height: Upto 3500mm Head plate = 355mm
 Overall height: Upto 4000mm Head plate = 375mm
 Overall height: Upto 4500mm Head plate = 400mm
- Minimum Side guide requirements:**
 Overall width: Upto 1400mm Guide = 38mm X 32mm Box section = 50mm
 Overall width: Upto 3000mm Guide = 50mm X 32mm Box section = 50mm
 Overall width: Upto 4000mm Guide = 63mm X 32mm Box section = 50mm
 Overall width: Upto 5000mm Guide = 63mm X 32mm Box section = 76mm
 Overall width: Upto 7000mm Guide = 76mm X 32mm Box section = 76mm
 Overall width: Upto 8000mm Guide = 100mm X 32mm Box section = 76mm

HAG Shutters & Grilles Ltd
 1 Oak Lane
 Fishponds
 Bristol
 BS5 7UY

Tel: 0117 9654888
 Fax: 0117 9657773
www.hag.co.uk
info@hag.co.uk

Disclaimer
 HAG operates a policy of continuous improvements, product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering.

Installation & Space requirements for standard Electric shutter

Scale: 1:20 @ A3