

Specification Sheets

Roller Garage Door





Title: Specification Sheet Seceuroglide Garage Door

Product Range	: Home & Office Security Rolling Garage Doors
Model	: Seceuroglide
LATH	
Description	: Seceuroglide is a double skin foam filled aluminium slat.
Common use	: High security. Domestic and Commercial Applications.
Dimensions	: Nominally 77mm high x 19mm thick.
Weight	: 6kg per square metre.
Finish	: White, brown, light beige, burgundy red, fir green or black & medium woodgrain (surcharges apply).
<u>SHUTTER BOX</u> Construction	Not supplied as standard, but if required. : Roll formed aluminium in two sections; top and bottom boxes. Bottom box removable for installation and maintenance and chamfered 45 degrees.
Box sizes	: Clear opening height (to underside of box): 2500mm box size 300mm 3500mm box side 350mm
Finish	: White, dark brown.
<u>GUIDE RAILS</u> Construction	: Ref: H75/UPH250 : Extruded aluminium with an integral box section for reinforcement and to facilitate fixing. Neoprene seals for quiet and smooth operation.
Dimensions	: 75mm wide x 34mm deep up to 4600mm wide 90mm wide x 34mm deep up to 5200mm wide
Finish	: Mill finish aluminium as standard.
Acoustics	: (Insulation 2.8 watts per m ² Kelvin w/m ² k Decibel reduction at 500HZ = 18 Decibel reduction at 1000MHZ = 25
<u>OPERATIONS</u> Single phase Electric	: A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating. Draw 240 volts and 0.5 – 2.5 amps dependant upon the shutter size.
Control	: Seceurosmart Remote Control unit with 2 Hand transmitters, photo cell safety device, internal manual override and light. Provision of a 13 amp fused spur is required for installation.
Disclaimer	HAG operates a policy of continuous improvement. Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering.