

Seceuro CD60 Built On

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Seceuro CD60 Built On



These roller shutter doors are manufactured from 60mm thick double walled aluminium, the CD60 model provides a higher degree of security. Spring loaded or electric operation available depending on requirements. Standard finishes of white, dark brown, cream, black or choose from RAL or BS colours at additional cost. Recommended maximum width up to 6,000mm.

Product Overview

Description

The Seceuro CD60 Built On roller shutters are constructed from a double skin extruded aluminium non-vented slat.

Common use

Seceuro CD60 Built On

For commercial windows and Shopfronts roller shutter doors

Maximum Width

6000mm

Dimensions

Nominally 55mm high x 14mm thick.

Weight

9kg per square metre.

Finish

White, brown. Bottom slat – white, dark brown alternative standard RAL or BS colours at extra cost.

Shutter Box Specification

Construction

Roll formed aluminium in two sections; top and bottom boxes. Bottom box removable for installation and maintenance and chamfered at 45°. The shutter box is assembled on die-cast aluminium endplates.

Box sizes

Clear opening height (to underside of box):

1595mm, box size 205mm

2750mm, box size 250mm

2900mm, box size 300mm

Finish

White, dark brown alternative standard RAL or BS colours at extra cost.

Guide Rail Specification

Construction

Standard guide rails: 60mm x 29mm x 3mm – 75mm x 29mm x 3mm dependant on width and height. Both with high-density pile 4mm brush seals.

Finish

White, dark brown alternative standard RAL or BS colours at extra cost.

Operational Specification

Spring Loaded

A counter balanced spring ensures controlled raising and Lowering with a key lock in-built at the bottom of the shutter for Security.

Single Phase Electric

Provision of a 13 amp fused spur is required for installation. A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating. Draw 240 volts and 0.5 – 2.5 amps dependant upon the shutter size

Control

Standard security keyswitch or rocker switch. Other controls are available on request.

Override

Seceuro CD60 Built On

A Manual override should be priced and ordered separately for Shutters which are to be installed on exit doorways to permit Operation in the event of a power failure. This is usually only Operable from only one side.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
