

Alulink G1-HD

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Alulink G1-HD



Providing a medium level of security, the apertures in the G1-HD roller shutter grille allows for through vision and ventilation. Manufactured from aluminium in a mill finish or choose from RAL or BS colours at additional cost. This roller grille is electrically operated with a choice of variety of controls. Recommended maximum width up to 6,000mm.

Product Overview

Description

An open-link security roller shutter grille offering both high visibility and excellent ventilation characteristics

Common use

Alulink G1-HD

Underground car park, shopping malls

Benefit of Product Range:

Double link arrangement for strength

High degree of ventilation, nominally 80% free air.

Maximises through-visibility

Added strength by integrated 'kick-zone' lower section

Maximum Width

Standard 6000mm (other widths by special consideration)

Dimensions

Portcullis pattern, nominally 300mm x 76mm cells (Option to specify stainless steel).

Finish

Mill finished aluminium, polyester powder coat colours are available.

Weight

15-kgs / sq metre

Finish

Standard mill aluminium, powder coat, stainless steel

Specification of Build

Aluminium tubes & links assembled on Aluminium rods to offer 300mm x 76mm apertures. (Option to specify stainless steel.)

Operation

Electric operation from a range of options. Integrated 240-volt tube motor for low frequency operation. Up to 100% duty rated 3-phase motor for high frequency applications.

Optional Extras

A range of operation, control and safety devices including photocell, safety edge, remote control, card reader, induction loop, traffic lights

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
