

Insurance Steel Doors SR2 SR3 SR4 SR5 Certified to LPS 1175 Series 7

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Insurance Steel Doors SR2 SR3 SR4 SR5 Certified to LPS 1175



Insurance certified range of high security steel doors. These steel security doors conform to LPS 1175 and are manufactured (by specification) to meet security and insurance levels SR2, SR3, SR4 or SR5, tested to LPS 1175 series 7 or PAS 24. Zinc-coated steel with a solid timber core. Available in standard or double openings at recommended maximum heights of 2,900 mm.

Product Overview

Operation

The insurance certified high security Steel Door range comes as a manual operation as standard.

Dimensions:

Single openings from 690mm to 1390mm

Double openings from 1290mm to 2600mm

All at heights up to 2900mm

Finish

This insurance certified range is available powder coated from a standard range of colours. Wood grain, PVC Laminate and Stainless steel are available.

Specification of Build

Dependant on the Security Level specified door blade and frame thickness range from 1.2mm to 3mm. A full range of

Insurance Steel Doors SR2 SR3 SR4 SR5 Certified to LPS 1175

hardware incorporating access and escape systems are available upon request, to conform to each Security Level specified. This product is also available with Secured by Design accreditation, tested to PAS 24.

The insurance rated range has a Steel Door Leaf thickness of 50mm and an infill composed of solid timber with integral steel stiffeners. This high security door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations. The frame is fitted with dog bolts as standard. The door is supplied with a standard 15mm rebated threshold and driveable thresholds available on request. The door blade is fitted with an anti jemmy as intragal.

Security

High Security triple point sash lock with high security cylinders and anti protected to reduce risk of key copying. HAG can supply an alternative high security multi point panic hardware for fire escape situation.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
