

Armourdoor AD60 Acoustic Soundproof Steel Door

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Armourdoor AD60 Acoustic Soundproof Steel Door



An acoustic soundproof steel door designed for soundproofing whilst providing a medium level of security. Tested to BS EN ISO 140-3:1995, the door is manually operated and can provide an acoustic reduction of 35 dB, 45 dB or 50 dB. Available in single or double openings at recommended heights of up to 2900 mm.

Product Overview

Operation

The armourdoor acoustic soundproof steel door comes as a manual operation.

Dimensions:

Single openings from 690mm to 1390mm

Armourdoor AD60 Acoustic Soundproof Steel Door

Double openings from 1290mm to 2600mm
All at heights up to 2900mm

Finish

The Armourdoor Acoustic Door AD60 is available powder coated from a standard range of colours. Wood grain, PVC Laminate and Stainless steel are available.

Specification of Build

The armourdoor acoustic soundproof steel door AD 60 has a leaf thickness of 56mm and an infill rock wool. Door Frame constructed from folded 1.6mm Zintec/aluzinc steel. The acoustic door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations. The frame is fitted with 1 dog bolt hinge as standard.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
