

Armourdoor AD70 Internal Steel Door

Technical Specifications



<https://www.hag.co.uk>
Advice Line 0800 072 3444

Armourdoor AD70 Internal Steel Door



Offering a medium level of security within the premises, the Armourdoor AD70 internal steel door has been designed for frequent use. Finish options include powder coating and a variety of wood grain laminate. Available in single or double openings at recommended heights of up to 2900 mm.

Product Overview

Operation

The ArmourdoorAD70 internal steel doors come as a manual operation.

Armourdoor AD70 Internal Steel Door

Dimensions:

Single openings from 690mm to 1390mm

Double openings from 1290mm to 2600mm

All at heights up to 2900mm

Finish

The Armourdoor Internal Steel Door AD70 is available powder coated from a standard range of colours. Wood Grain laminate – Nordik Oak, Ash, Mahogany, Teak, Cherry, Virgin White, Golden Oak, Magic Oak.

Specification of Build

The Steel door has a leaf thickness of 48mm. The core of the steel door is honeycomb as standard, with the option of solid timber or rock wool. Door Frame constructed from folded 1.6mm Magnelis steel. The internal steel door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations. The Door is supplied with a standard driveable threshold.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

