

Ali Glyde W10

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Ali Glyde W10



A manually operated sliding shutter designed for internal use in areas requiring a good level of security. Micro-perforated steel panels allow for ventilation and through vision. A selection of finishes available and Adams Rite mortice lock fitted as standard. Suitable for curved apertures. No maximum span. Recommended maximum height up to 4,500mm.

Product Overview

Description

The Ali Glyde W10 sliding folding shutter is constructed from perforated steel and provides a degree of ventilation and vision yet maintaining a good level of security. The W10 is manufactured from micro perforated steel panels to form a semi solid curtain that enables closure over large and curved areas with intermediate locking points into flush floor sockets.

Common use

The Ali Glyde W10 sliding shutter is best installed in internal retail outlets and areas requiring designation such as shopping malls, airports, in store concessions and railway stations.

Dimensions

152mm vertical Sections with aluminium hinges

Ali Glyde W10

Weight

10kg Per M2

Finish

Standard Finishes Silver, White, Medium Bronze, light Bronze or Black.

Top Track

Aluminium 34mm x 42mm High No requirement for bottom track

Curved Apertures

This Product is highly flexible to provide limitless options for imaginative design lay outs to suit any shape or length.

Stacking Size

Approximately 15% of overall length

Locking

Adams rite mortice lock with intermediate post's incorporating drop bolts locating into flush floor sockets.

Operation

Manual sliding Operation

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
