

Ali Glyde W20

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Ali Glyde W20



A manually operated sliding shutter designed for internal use. Aluminium panels with a tempered glass infill allows for through vision without compromising security or aesthetics. A selection of finishes are available and Adams Rite mortice lock fitted as standard. Suitable for curved apertures. No maximum span. Recommended maximum height up to 4,500mm.

Product Overview

Description

The Ali Glyde W20 sliding folding shutter is a top track supported sliding folding shutter system using aesthetically pleasing and durable design features. Manufactured from aluminium panels with tempered glass infill that provides a good degree of vision and prevents any petty pilfering of goods behind the screen when closed and locked off.

Common use

Installation of the Ali glyde W20 sliding shutter is usually in internal retail outlets, shopping malls, airports, bank lobbies, railway stations and areas that require a high degree of finish.

Dimensions:

152mm vertical sections with aluminium hinges

Weight:

Ali Glyde W20

12kg per square metre

Finish:

Standard finishes for frame are silver, white, medium bronze, light bronze or black.

Top Track:

Aluminium 34mm x 42mm high. No requirement for bottom track.

Curved Apertures:

This product is highly flexible to provide limitless options for imaginative design layouts to suit any shape or length.

Stacking Size:

Approximately 15% of overall length.

Locking:

Adams Rite mortice lock with intermediate posts incorporating drop bolts locating into flush floor sockets.

Operation:

Manual sliding folding operation

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
