

EV Curtain

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

EV Curtain



Durable PVC strip curtain fixed overhead to allow for quick entrances and exits in busy industry premises. Clear PVC strip curtains allow for through vision while offering a level of thermal protection. Options include removal strips, swing, or side sliding PVC strips. Made to order so will be bespoke to the aperture. Available in any width.

Common use

Industrial Units, Door Ways Cold Stores (Overlapping amount will vary for application).

Dimensions

PVC Strips thickness ranging from 2mm to 4mm. 200mm wide to 400mm wide strips.

Finish

PVC Strip curtain clear midsection with optional colours for end sections if required.

EV Curtain

Insulation

The recommended temperature range in use is -5°C to +60°C.

Overhead Rail

Supported by a galvanised or stainless steel frame.

Overhead Fixing Options

Removable Strips. Swing Strips. Side Sliding Strips.

Made to Order

All our PVC strip curtains are custom made to order and are supplied with the header rail fixing system to suit your particular door specification. We also provide a strip replacement service to maintain the integrity of your curtains throughout their working life.

Product specification may change and it is advisable to consult with [HAG technical advisors](#) before specifying or ordering. HAG operates a policy of continuous improvement.
