


Armourdoor Louvred Steel Door AD30

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444



Description

Armourdoor Louvred Steel Door AD30 is a high security door with louvred blades set 45° to allow gases and airflow through the door.

Common use

The AD 30 is commonly installed in generator rooms, swimming pools, plant rooms and boiler rooms and other commercial areas that require specific ventilation.

Dimensions

Single openings from 690mm to 1390mm. Double openings from 1290mm to 2600mm. All at heights up to 2900mm

Security Level

Medium Security

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Armourdoor Louvred Steel Door AD30



Product Overview

Operation

Manual

Finish

The Armourdoor AD30 louvred steel door is available powder coated from a standard range of colours.

Specification of Build

HAG louvred doors are made to order and can be offered either fully louvred as a steel equivalent to an aluminium louvred door or as a steel door with louvre panels inset to allow ventilation.

The louvred door has a leaf thickness of 48mm.

The Steel door blades made from 1.2mm corrosion resistant Zintec/Aluzinc as standard. The blades are set at 45° and mounted at 50mm x 50mm angle frame, which is supported by a box section sub-frame.

The core of the steel door is a honeycomb core as standard, with the option of solid timber or rock wool.

The louvred door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations.

The frame is fitted with 1 dog bolt per hinge as standard.

The Door is supplied with a standard 15mm rebated threshold, driveable thresholds available on request.

Optional Extras:

Louvred over panels and side panels are available

A galvanised bird and vermin mesh can be supplied

Panic bolts / Latch

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
