

# Armourdoor Fire Exit Steel Door AD10

## Technical Specifications



[www.hag.co.uk](http://www.hag.co.uk)  
Advice Line 0800 072 3444

# Armourdoor Fire Exit Steel Door AD10



## Product Range

Armourdoor Fire Exit Steel Door AD10 is constructed from 1.2mm zinc protected steel sheets joined together in a bonding process with a choice of infill e.g. honeycomb core, rock wool or solid timber dependant on insulation and security requirements. The Door is supported by a 1.6mm profiled zinc protected steel frame.

## Common Use

Fire exit doors to be used by the general public too provide safe and effective escape through the doorway with minimal effort without prior knowledge of operation. General applications can be offices, shops, sports centres, schools and universities.

## Typical Uses

Single openings from 690mm to 1350mm. Double openings from 1290mm to 2800mm. All at heights up to 2900mm

## Security Level

Medium / High

# Armourdoor Fire Exit Steel Door AD10



## Product Overview

### Operation

Manual

### Finish

The Armourdoor AD10 fire exit steel door is available powder coated from a standard range of colours. Wood grain, PVC Laminate and Stainless steel are available.

### Specification of Build

The fire exit door has a leaf thickness of 48mm.

The core of the steel door is a honeycomb core as standard, with the option of solid timber or rock wool.

Door Frame constructed from folded 1.6mm Zintec/aluzinc steel.

The fire exit door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations.

The frame is fitted with dog bolt for hinge as standard.

The Door is supplied with a standard 15mm rebated threshold; driveable thresholds available on request.

### Panic Hardware

Fire Exit Doors are supplied with a Single or 2 Point Panic Bar or Push Pad as standard. A comprehensive range of hardware including rim locks, mortice locks, night latches and dead locks are available to meet site specific needs. Hardware is factory fitted to allow rapid site installation \*note minimal site assembly may be required for double doors & hardware items such as door closers etc

---

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

---

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---



**Product**: Armourdoor Fire Exit Steel Door AD10  
**Operation**: Manual  
**Infill**: Honeycomb  
**Panic Hardware**: Exidor 294 panic bolt  
**Threshold**: Std  
**Frame Type**: Type C  
**Fixing**: Reveal fixed  
**Finish**: Primer Finish (PPC options available contact office to discuss)

Scale: NTS @ A3

**HAG Shutters & Grilles Ltd**  
 1 Oak Lane  
 Fishponds  
 Bristol  
 BS5 7UY

Tel: 0117 9654888  
 Fax: 0117 9657773  
[www.hag.co.uk](http://www.hag.co.uk)  
[info@hag.co.uk](mailto:info@hag.co.uk)

**Disclaimer**  
 HAG operates a policy of continuous improvements, product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering.

## Installation & Space requirements for standard Fire Exit Steel Door