

HAG Bi Folding Speed Gate

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

HAG Bi Folding Speed Gate



Product Range

HAG Bi Folding Speed Gate

What Is It Made From

The HAG Bi folding Speed gates are made from Mild steel

Typical Uses

Typical uses of this product is car parks or restricted high security areas

Security Level

This product offers High security

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

HAG Bi Folding Speed Gate



Product Overview

Description

A mild steel speed gate with electric operation closing in under 2 seconds

Benefit of Product Range

Speed of opening is less than two seconds to ensure high security whilst giving minimal operating noise which is ideal for high occupancy dwellings.

Low maintenance, high reliability and Comprehensive safety features.

Common Use

A product applicable to premises requiring secure, high frequency vehicle access, particularly underground car parks of high density residential/office developments.

Maximum Width

Single bi-fold gate 5500mm, double bi-fold gate 11000mm

Dimensions

Maximum height 2200mm

Finish

Galvanised as standard with a choice of standard powder-coat colours

Specification of Build

Standard Build is with a 200 x 200 steel posts

Gate is framed in 60 x 60 box section with a 30 x 30 post with 100mm centres.

Typical Arrangements

Single bi fold Gate or a double bi fold gate

Operation

Specified by user at time of quoting. Card reader, key, radio control, etc.

Safety

Photo cell and safety edge as standard available

Optional Extras

Card readers, Induction loop radio control, car park vehicle detection.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
