

Seceuro Glide Garage Doors

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444

Seceuro Glide Garage Doors



What is it made from

Securo Glide Garage Door is a foam filled aluminium product.

Typical Uses or Specific Use

Typical uses are a Domestic Garage Doors.

Security Level

Medium to high Security.

Benefit of product range

High insulation Value, quiet operation / smooth running with choice of standard colours.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Seceuro Glide Garage Doors



Product Overview

Description

Seceuro Glide, Seceuroglide is a double skin foam filled aluminium slat.

Common use

Garage Doors

Maximum Width

5400mm

Dimensions

Nominally 77mm high x 19mm thick.

Weight

6kg per square metre.

Finish

White, brown, light beige, burgundy red, fir green or black & medium woodgrain (surcharges apply).

Shutter Box Specification

Construction

Roll formed aluminium in two sections; top and bottom boxes.

Bottom box removable for installation and maintenance and chamfered 45 degrees.

Box sizes

Clear opening height (to underside of box):

2500mm box size 300mm

3500mm box side 350mm

Finish

White, dark brown, Alternative standard RAL or BS colours at an extra cost.

Guide Rail Specification

Construction

Extruded aluminium with an integral box section for reinforcement and to facilitate fixing.

Neoprene seals for quiet and smooth operation.

Dimensions

75mm wide x 34mm deep up to 4600mm wide

90mm wide x 34mm deep up to 5200mm wide

Finish

White, brown, light beige, burgundy red, fir green or black.

Acoustics

(Insulation 2.8 watts per m² Kelvin w/m²k)

Decibel reduction at 500HZ = 18

Decibel reduction at 1000MHZ = 25k.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk

Seceuro Glide Garage Doors



Operational Specification

Single Phase Electric

Provision of a 13 amp fused spur is required for installation. A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating. Draw 240 volts and 0.5 - 2.5 amps dependant upon the shutter size.

Control

Seceurosmart Remote Control unit with 2 Hand transmitters, Wireless Safety edge, internal manual override and light

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

For further information about this product please call the HAG advice line on 0800 072 3444 or email info@hag.co.uk
