

Product: CD150 Foam Filled Aluminium Lath
Operation: Spring & Locking system
Fixing: Reveal fixed or Face fixed
Finish: White (Ral 9010) or Brown (Ral 8014)

Head plate sizes:
 Overall height: Upto 1600mm Head plate = 165mm
 Overall height: Upto 2000mm Head plate = 180mm
 Overall height: Upto 2800mm Head plate = 205mm

Minimum Side guide requirements:
 Overall width: Upto 3400mm Guide = 53mm X 22mm


Maximum width: 3400mm
Maximum height: 2800mm
Curtain weight: 4.5kgs per m2

HAG Shutters & Grilles Ltd
 1 Oak Lane
 Fishponds
 Bristol
 BS5 7UY

Tel: 0117 9654888
 Fax: 0117 9657773
www.hag.co.uk
info@hag.co.uk

Installation & Space requirements for standard Manual shutter

Scale: 1:20 @ A3



Product : CD150 Foam Filled Aluminium
Operation: Single phase tube motor with override
Operator: security keyswitch
Power requirements: 13amp fused spur within 1 metre of opening
Fixing: Reveal fixed or Face fixed
Finish: White(Ral 9010) or Brown (Ral 8014) as standard

Head plate sizes:
 Overall height: Upto 1600mm Head plate = 165mm
 Overall height: Upto 2000mm Head plate = 180mm
 Overall height: Upto 2800mm Head plate = 205mm

Minimum Side guide requirements:
 Overall width: Upto 3400mm Guide = 53mm X 22mm

Maximum width: 3400mm
Maximum height: 2800mm
Curtain weight: 4.5kgs per m2

Scale: 1:20 @ A3

Installation & Space requirements for standard Electric shutter

HAG Shutters & Grilles Ltd
 1 Oak Lane
 Fishponds
 Bristol
 BS5 7UY

Tel: 0117 9654888
 Fax: 0117 9657773
www.hag.co.uk
info@hag.co.uk